

'G'- CLAMPS - SUPER GRADE - UNBREAKABLE

DAWN G-Clamps are cast in ductile iron and are unbreakable. They have heavy ribbed frame for strength and durability. This popular type has high quality zinc plated Whitworth threaded screw with swivel button. The swivel button enables the user to apply pressure evenly on angular workpieces. For metal, woodworking and general use.

PART NO	SIZE - JAW OPENING MM	TYPE	THROAT DEPTH MM	WT KGS	FRAME PROOF LOAD KGS
61152	75	SUPER-GRADE	45	0.6	500
61153	100	SUPER-GRADE	50	1.0	750
61155	150	SUPER-GRADE	70	2.0	1100
61156	200	SUPER-GRADE	85	3.3	1300
61157	250	SUPER-GRADE	95	3.9	1750
61158	300	SUPER-GRADE	100	4.3	2100



'G'- CLAMPS - FORGED - ULTRA STRONG

Ultra strong drop forged steel clamp whose slim section permits use in confined spaces. Ideally suited to heavy engineering, including metal fabrication and welding. Painted Blue.

PART NO	SIZE - JAW OPENING MM	TYPE	THROAT DEPTH MM	WT KGS	FRAME PROOF LOAD KGS
61166	75	FORGED STEEL	50	0.5	2050
61167	100	FORGED STEEL	60	0.7	2350
61168	150	FORGED STEEL	75	1.6	3600
61169	200	FORGED STEEL	85	3.4	5750



ONE HANDED 'G' CLAMPS

This unique one Hand G Clamp Leaves one hand free to hold items being clamped whilst the other operates the clamp by means of a **special knurled nut**.

- 'I' beam frame section ensures maximum frame loading and resistance to twisting
- Two start rolled thread for quick clamping
- Square frame for maximum clamp usage

PART NO.	SIZE - JAW OPENING MM	THROAT DEPTH MM	WT KGS
DW73040	100	65	1.0
DW73060	150	80	1.5
DW73080	200	90	2.2



STAINLESS STEEL 'G' CLAMPS - 316 MARINE GRADE

- Made from Marine Grade 316 Stainless Steel
- Corrosion Resistant and Non Magnetic
- High quality Whitworth thread
- Swivel pad applies pressure evenly on angular work pieces
- Ideal in marine and specialist chemical environments

PART NO	SIZE - JAW OPENING	TYPE	THROAT DEPTH	WT KGS
61152-GSS	75	Cast	45	0.6
61152-FSS	75	Fabricated	45	0.5
61153-GSS	100	Cast	50	1.0
61153-FSS	100	Fabricated	50	0.9
61155-GSS	150	Cast	70	2.0
61155-FSS	150	Fabricated	70	1.9



Fabricated



Cast